

## P/N: 29360-200

### Copyright

© 2017, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

### Document identity

Publ. No.: 29360-200

Release:

Commit: 44541

Language: en-US

Modified: 2017-08-29

Formatted: 2017-09-15

### Website

<http://www.flir.com>

### Customer support

<http://support.flir.com>

### Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to [exportquestions@flir.com](mailto:exportquestions@flir.com) with any questions.



<b>Detector data</b>	
Detector Type	FLIR Indium Antimonide (InSb)
Spectral Range	1.0 – 5.0 $\mu\text{m}$
Resolution	640 x 512
Detector Pitch	15 $\mu\text{m}$
Thermal Sensitivity/NETD	< 18 mK
Well Capacity	7.2 M electrons
Operability	> 99.8% (> 99.95% typical)
Sensor Cooling	Closed cycle rotary
<b>Electronics</b>	
Readout Type	Snapshot
Readout Modes	Asynchronous integrate while read, Asynchronous integrate then read
Synchronization Modes	Sync In, Sync Out
Image Time Stamp	Yes
Integration Time	480 ns to Full Frame
Pixel Clock	50 MHz
Frame Rate (Full Window)	Programmable; 0.0015 Hz to 60 Hz
Subwindow Mode	640x512, 320x256, 160x128
Dynamic Range	14-bit
On-Camera Image Storage	None
Radiometric Data Streaming	Gigabit Ethernet (GigE Vision)
Standard Video	NTSC or PAL composite
Command and Control	GenICam (GigE)
<b>Temperature Measurement</b>	
Standard Temperature Range	-20°C to 350°C (-4°F to 662°F)
Optional Temperature Range	Up to 1,500°C (2,732°F), Up to 3,000°C (5,432°F)
Accuracy	<ul style="list-style-type: none"> <li><math>\pm 1^\circ\text{C}</math> or <math>\pm 1\%</math> of reading: <ul style="list-style-type: none"> <li>• 0°C to +3000°C (25 mm, 50 mm, 100 mm lenses)</li> </ul> </li> <li><math>\pm 2^\circ\text{C}</math> or <math>\pm 2\%</math> of reading: <ul style="list-style-type: none"> <li>• -20°C to 0°C (25 mm, 50 mm, 100 mm lenses)</li> </ul> </li> </ul>



## FLIR A6600

P/N: 29360-200

© 2017, FLIR Systems, Inc.

#29360-200; r. /44541; en-US

<b>Optics</b>	
Camera f/Number	f/2.5
Available Lenses (Uses FLIR HDC Optics)	25 mm, 50 mm, 100 mm
Close-up Lenses/Microscopes	No microscopes available
Lens Interface	FLIR HDC (4-tab bayonet)
Focus	Manual
Filtering	Behind-lens mount for standard 1 inch diameter filters

  

<b>Image/Video Presentation</b>	
Palettes	Selectable 8-bit
Automatic Gain Control	Manual, Linear, Plateau equalization, ROI, DDE
Overlay	Customizable (Date, Integration time, Internal temp, Frame rate, Sync mode, Cooler hours)
Video Modes	NTSC, PAL
Digital Zoom	1x, 4x

  

<b>General</b>	
Operating Temperature Range	-20°C to 50°C (-4°F to 122°F)
Shock/Vibration	40 g, 11 msec ½ sine pulse/4.3 g RMS random vibration, all 3 axes
Power	24 VDC (< 21.25 W steady state)
Weight w/o Lens	2.3 kg (5 lbs)
Size (L x W x H) w/o Lens	216 x 102 x 109 mm (8.5 x 4.0 x 4.3 in)
Mounting	<ul style="list-style-type: none"><li>• 2 x ¼" -20 tapped holes</li><li>• 1 x 3/8"-16 tapped hole</li><li>• 4 x 10-24 tapped holes</li></ul>

### Supplies & accessories:

- 29425-100; Lens 1-5 um 100 mm f/2.5 HDC Bayonet
- 29425-025; Lens 1-5 um 25 mm f/2.5 HDC Bayonet
- 29425-050; Lens 1-5 um 50 mm f/2.5 HDC Bayonet





